

Pulse Counter

Featuring LoRaWAN®

EM300-DI

The Milesight logo is displayed in a stylized, italicized font. The letter 'M' is blue, and the letters 'ilesight' are black.

EM300-DI is a compact LoRaWAN® pulse counter which transforms traditional water meters into wireless intelligent meters. With IP67 waterproof design, it is applicable in various harsh application environments.

In addition to LoRaWAN® technology with low power consumption, it has a built-in high-capacity battery available for several years without replacement. Moreover, EM300-DI is compatible with both Milesight LoRaWAN® gateway and Milesight IoT Cloud to achieve remote monitoring and visualized smart data management to achieve the purpose of saving water. It is suitable for both indoor and outdoor applications such as agricultural irrigation, industrial water use, property meter reading and numerous scenarios.

◆ Features

- Flexible counting configuration to enable, stop, clear accumulated values
- Support digital filtering that filters interference signals to ensure more accurate counters
- Embedded with temperature and humidity sensors for environment monitoring
- IP67 waterproof enclosure for harsh environment applications
- Ultra-wide-distance transmission up to line of sight of 10km
- Store more than 2200 historical records and support retransmission to prevent data loss
- A built-in 4000 mAh replaceable battery and works for 5 years without replacement
- Equipped with NFC for easily configuration
- Compliant with standard LoRaWAN® gateways and network servers

- Quick and easy management with Milesight IoT Cloud solution

◆ Specifications

Wireless Transmission	
Technology	LoRaWAN®
Frequency	CN470/IN865/RU864/EU868/US915/AU915/KR920/AS923-1&2&3&4
Tx Power	16dBm(868)/20dBm(915)/19dBm(470)
Sensitivity	-137dBm @300bps
Mode	OTAA/ABP Class A
Measurement	
GPIO	
Port	1 × GPIO Interface, Dry Contact
Work Mode	Pulse Counter, Digital Input
Cable Length	1 m (Customizable)
Applicable Meters	Reed switches meters or any other passive pulse meters
Temperature	
Range	-30°C to + 70°C
Accuracy	0°C to + 70°C (+/- 0.3°C), -30°C to 0°C (+/- 0.6°C)
Resolution	0.1°C
Humidity	
Range	0% to 100% RH
Accuracy	10% to 90% RH (+/- 3%), below 10% and above 90% RH (+/- 5%)
Resolution	0.5% RH
Operation	
Power On & Off	NFC, Power Button (Internal)
Configuration	NFC Configuration via Mobile App
Physical Characteristics	
Power Supply	1 × 4000 mAh ER18505 Li-SOCL ₂ Battery (extendable to 2 batteries)
Battery Life*	5 years (10 min interval + 12 pulse counts per day)
Operating Temperature	-30°C to +70°C
Relative Humidity	≤95% (non-condensing)
Material & Color	ABS + PC, White
Ingress Protection	IP67
Dimension	105.6 × 85.2 × 27 mm (4.15 × 3.35 × 1.06 in)

Installation

Screw Mounting

* Tested under laboratory conditions and for guideline purposes only.

